

TECHNICAL DATA SHEET



AEROSOLS



Lubricate - Oil – Grease GREASE SPRAY

WIKO GREASE SPRAY guarantees a long-term functional reliability of expensive installations by reducing downtimes and repairs. WIKO GREASE SPRAY serves to grease and lubricate, e.g. gears, racks, wire ropes, open gears or driving rods.

- High capillary action and excellent adhesive strength
- Long-term resistance to water
- Prevents corrosion
- Reduction of down-times and repairs as well as usage of other lubricants
- Temperature range: -40 °C to +150 °C (shortly up to +250 °C)

Application area

- Lubrication of heavily stressed machine parts, e.g. slide bearings, ball bearings, hinge supports, shafts and guides in sectors like industry, vehicle construction, shipping
- Perfectly suited as lubrication for battery terminals
- Lubrication of gear wheels, toothed racks, chains and steel cables, open gear mechanisms and driving rods
- Easy to apply product for a long-term lubrication

Sizes / article number

400 ml can

AFES.D400

Application

The designated surfaces have to be free of dirt, rust, oil and grease (we recommend the usage of a suited WIKO cleaner, e.g. WIKO INDUSTRIAL QUICK CLEANER (art. No. AISR.D400)). Shake the aerosol can intensively for approx. 2 minutes. Perform a test spraying. Afterwards, apply the spray evenly from a range of 20 to 30 cm and let it air dry approx. 10 minutes. After usage, turn the aerosol can upside-down and spray until only propellant gas emerges out of the nozzle.

Storage & Durability

The shelf life is, at the optimum storage temperature of +5 °C to +25 °C in the closed original container, a maximum of 12 months. A higher storage temperature leads to a significantly lower durability. The storage temperature must not fall below +5 °C.

Note:

Please note the information and notes in our respective safety data sheets. The data contained herein are for informational purposes only and are believed to be accurate to the best of our knowledge. We assume no liability for the results. For optimum functionality of the adhesive system, please only use the cartridge and mixer systems tested and released by GLUETEC. The product is only suitable for professional and experienced users. It is the user's own responsibility to take precautions to protect property and people from the hazards that may be encountered in handling and using these products. Accordingly, GLUETEC specifically disclaims any warranty, expressed or implied, including any warranty or suitability commitments for a particular purpose. In particular, GLUETEC disclaims all liability for consequential or indirect damages of any kind.