

TECHNICAL DATA SHEET



AEROSOLS



Cleaning and care **CONTACT CLEANER**

WIKO CONTACT CLEANER cleans and degreases old encrustations which can lead to electricity loss and breakdowns. The remaining active substances are based on mineral oil and therefore provide a conserving effect that prevents an oxidation of the cleaned contacts.

- Effective cleaning, degreasing and dissolving of old impurities
- Lasting conservation of cleaned contacts
- Prevention of electricity loss and breakdowns
- Excellent infiltration and displacement of water
- Perfectly suited for sensitive component parts and connections
- Free of FCKW, HFCKW and halogenated solvents
- Filled with carbon dioxide as propellant gas

Application areas

- Cleaning and degreasing of contacts
- Dissolving of encrustations
- Conservation of cleaned contacts
- Contacts, fuses, cable connections, plug connectors, distributor caps and many more

Sizes / article number

400 ml can

AKTR.D400

Application

Shake the aerosol can intensively before the application and perform a test spraying. Apply the spray crosswise from a range of 20 to 30 cm onto the dirty contacts or contacts that are to be conserved. Let the spray evaporate and wipe off excess material with a clean fabric if necessary. In case of heavy dirt residues, repeat the procedure several times. Note: Test compatibility before extensive application on a concealed spot, especially in combination with plastics.

Storage & Durability

The shelf life is, at the optimum storage temperature of +5 °C to +25 °C in the closed original container, a maximum of 12 months. A higher storage temperature leads to a significantly lower durability. The storage temperature must not fall below +5 °C.

Note:

Please note the information and notes in our respective safety data sheets. The data contained herein are for informational purposes only and are believed to be accurate to the best of our knowledge. We assume no liability for the results. For optimum functionality of the adhesive system, please only use the cartridge and mixer systems tested and released by GLUETEC. The product is only suitable for professional and experienced users. It is the user's own responsibility to take precautions to protect property and people from the hazards that may be encountered in handling and using these products. Accordingly, GLUETEC specifically disclaims any warranty, expressed or implied, including any warranty or suitability commitments for a particular purpose. In particular, GLUETEC disclaims all liability for consequential or indirect damages of any kind.