

AEROSOLS



Maintenance & repair LEAK DETECTOR

WIKO LEAK DETECTOR enables an effortless detection of leaky spots at pressurized screw connections, flanged joints, pipes and welds.

- Easy controlling of leaking spots
- Product is non-flammable and non-corrosive
- Temperature range: 0 °C to +50 °C

Application areas

- Block valve, fittings, autogenous welding equipment
- Brake system, camping stove, Bunsen burners
- Pressure tank, compressed-air connections, pressure controller, flow heater
- Fire extinguishers, beads, cylinder bank
- Gas supply, gas stove, gas radiators, gas transporters, gas heating
- Hose connections, gas bottles, diving equipment
- Valves, screw joints, service pipes

Sizes / article number

300 ml can

ALSU.D400

Application

Shake the aerosol can intensively before the application. Uncover the spots suspected to be leaking and spray (pressurize lines if necessary). Always keep the can in a vertical position. In case of leakage, an extremely strong foam formation will show the leaky spot. Carefully clean plastic pipes with water shortly after the detection procedure. Caution: Must not be used to test oxygen-carrying lines.

Storage & Durability

The shelf life is, at the optimum storage temperature of +5 °C to +25 °C in the closed original container, a maximum of 12 months. A higher storage temperature leads to a significantly lower durability. The storage temperature must not fall below +5 °C.

Note:

Please note the information and notes in our respective safety data sheets. The data contained herein are for informational purposes only and are believed to be accurate to the best of our knowledge. We assume no liability for the results. For optimum functionality of the adhesive system, please only use the cartridge and mixer systems tested and released by GLUETEC. The product is only suitable for professional and experienced users. It is the user's own responsibility to take precautions to protect property and people from the hazards that may be encountered in handling and using these products. Accordingly, GLUETEC specifically disclaims any warranty, expressed or implied, including any warranty or suitability commitments for a particular purpose. In particular, GLUETEC disclaims all liability for consequential or indirect damages of any kind.