

TECHNICAL DATA SHEET



AEROSOLS



Lubricate - Oil – Grease MULTIFUNCTIONAL SPRAY

WIKO MULTIFUNCTIONAL SPRAY is a silicone-free, low viscosity oil for lubrication and maintenance of most diverse metal parts. The spray is applied in the areas of car industry, machine building, metalworking shops, hobby and households.

- Fast and easy loosening of seized up connections like screws, nuts and bolts
- Reliable protection against corrosion
- Eliminates squeaking and creaking

Application areas

- Lubrication of threads, hinges, pulleys, springs, water taps, door and window hinges, swivel chairs, door locks, zip fastener, precision mechanics and electrical connections (switches, plugs, couplings and cables)
- Suppression of water from metal surfaces, e.g. at electrical contacts and power outlets, car ignition systems, tools, motorcycles and outboard engines
- Easy removal of grease, tar, rubber and adhesive residues. Creates a protective film against corrosion and rust. The product is suited for all metals, engines and vehicles of all kinds
- Loosens rusted, corroded and seized metal connections like screws, nuts, bolts, etc.
- First-rate capillary properties and penetrability

Sizes / article number

400 ml can AMFS.D400

Application

The designated surfaces have to be free of dirt, rust, oil and grease (we recommend a WIKO cleaner, e.g. WIKO INDUSTRIAL QUICK CLEANER art. No. AISR.D400). Shake the aerosol can intensively. Perform a test spraying. Afterwards, apply the spray thoroughly.

Storage & Durability

The shelf life is, at the optimum storage temperature of +5 °C to +25 °C in the closed original container, a maximum of 12 months. A higher storage temperature leads to a significantly lower durability. The storage temperature must not fall below +5 °C.

Note:

Please note the information and notes in our respective safety data sheets. The data contained herein are for informational purposes only and are believed to be accurate to the best of our knowledge. We assume no liability for the results. For optimum functionality of the adhesive system, please only use the cartridge and mixer systems tested and released by GLUETEC. The product is only suitable for professional and experienced users. It is the user's own responsibility to take precautions to protect property and people from the hazards that may be encountered in handling and using these products. Accordingly, GLUETEC specifically disclaims any warranty, expressed or implied, including any warranty or suitability commitments for a particular purpose. In particular, GLUETEC disclaims all liability for consequential or indirect damages of any kind.