

TECHNICAL DATA SHEET



AEROSOLS



Maintenance & repair RUST DISSOLVER WITH MOS2

WIKO RUST DISSOLVER WITH MOS2 is a reliable tool for maintenance, repair and production. The rust remover not only quickly and reliably eliminates the problems of stuck, corroded fittings, but can also be used as a lubricant and contact agent. WIKO RUST DISSOLVER WITH MOS2 is able to penetrate even the smallest interspaces due to its high capillary action and good flow properties.

- Corrosion-resistant bonds prevent new long-term corrosion
- Easy finding and controlling of leaking spots
- Temperature range: 0 °C to +50 °C
- Product is non-flammable and non-corrosive

Application areas

- Protects against corrosion, greases anti-friction surfaces and stops creaking noises
- Cleaning and maintenance of brake leverages, Bowden cables and all types of chains
- Dissolving of corroded or seized connections, screw joints, nuts and bolts

Sizes / article number

400 ml can

AROL.D400

Application

Shake the aerosol can intensively before the application. Spray the designated spots and cover the whole area. Wait a few minutes for the product to react on the surface, afterwards, the sprayed parts can be dissolved.

Storage & Durability

The shelf life is, at the optimum storage temperature of +5 °C to +25 °C in the closed original container, a maximum of 12 months. A higher storage temperature leads to a significantly lower durability. The storage temperature must not fall below +5 °C.

Note:

Please note the information and notes in our respective safety data sheets. The data contained herein are for informational purposes only and are believed to be accurate to the best of our knowledge. We assume no liability for the results. For optimum functionality of the adhesive system, please only use the cartridge and mixer systems tested and released by GLUETEC. The product is only suitable for professional and experienced users. It is the user's own responsibility to take precautions to protect property and people from the hazards that may be encountered in handling and using these products. Accordingly, GLUETEC specifically disclaims any warranty, expressed or implied, including any warranty or suitability commitments for a particular purpose. In particular, GLUETEC disclaims all liability for consequential or indirect damages of any kind.