

# TECHNICAL DATA SHEET



## AEROSOLS



## Lubricate – Oil – Grease SILICONE SPRAY

WIKO SILICONE SPRAY is an ideal lubricant and release agent for production and maintenance. The grease-free spray is used for both protection and care, thus ensuring a long-lasting release film or a good surface finish. Outstanding lubrication on plastic, rubber and metal parts.

- Reliable protection against oxidation and corrosion
- Waterproof and antistatic
- Good surface properties
- Clean lubrication film that does not harsh
- Temperature range: -30 °C to +150 °C (shortly up to +180 °C)

## Application areas

- Protects electrical contacts against moisture
- Rubber parts are maintained with the effect that they do not become brittle, freeze or adhere
- Plastic parts receive high gloss and do not become fragile
- Restores the smooth mobility of retractable roofs, seat slides and safety belt reels
- Restores the mobility of seized or squeaking parts
- Excellent release agent for casting and injection molding
- Suits as an assembly help for hose connections

## Sizes / article number

400 ml can

ASIS.D400

## Application

The designated surfaces have to be free of dirt, rust, oil and grease (we recommend the usage of a suited WIKO cleaner, e.g. with WIKO INDUSTRIAL QUICK CLEANER (art. No. AISR.D400)). Shake the aerosol can intensively. Perform a test spraying. Afterwards, apply the spray crosswise from a range of 20 to 30 cm and rub the product with a smooth fabric.

## Storage & Durability

The shelf life is, at the optimum storage temperature of +5 °C to +25 °C in the closed original container, a maximum of 12 months. A higher storage temperature leads to a significantly lower durability. The storage temperature must not fall below +5 °C.

### Note:

Please note the information and notes in our respective safety data sheets. The data contained herein are for informational purposes only and are believed to be accurate to the best of our knowledge. We assume no liability for the results. For optimum functionality of the adhesive system, please only use the cartridge and mixer systems tested and released by GLUETEC. The product is only suitable for professional and experienced users. It is the user's own responsibility to take precautions to protect property and people from the hazards that may be encountered in handling and using these products. Accordingly, GLUETEC specifically disclaims any warranty, expressed or implied, including any warranty or suitability commitments for a particular purpose. In particular, GLUETEC disclaims all liability for consequential or indirect damages of any kind.