

TECHNICAL DATA SHEET



AEROSOLS



Lubricate - Oil - Grease CHAIN SPRAY WITH MOS2

Synthetic and transparent adhesive lubricant for the permanent inside and outside lubrication of all kinds of highly stressed chains and wipe ropes. WIKO CHAIN SPRAY WITH MOS2 is resistant to water, displaces the moisture and has a preserving effect.

- Sustained lubrication of chains, joints and clutches
- Permanent protection against corrosion
- excellent flow properties and gap penetration capability
- Temperature range: -35 °C to +200 °C

Application areas

- All kinds of chains, joints, clutches, wipe ropes and many more
- Gear wheels and worm gears
- Roller bearings and ball bearings
- O-rings

Sizes / article number

400 ml can

AKTS.D400

Application

Remove any grease residues before use, e.g. pretreat with WIKO INDUSTRIAL CLEANER (art. no. AISR.D400). Shake the can intensively before use. Sprinkle sliding surfaces or the outward-facing gaps sufficiently from a distance of approx. 20 cm. Wait until penetration and spray again if necessary. Commissioning approx. 10 minutes after spraying or venting.

Storage & Durability

The shelf life is, at the optimum storage temperature of +5 °C to +25 °C in the closed original container, a maximum of 12 months. A higher storage temperature leads to a significantly lower durability. The storage temperature must not fall below +5 °C.

Note:

Please note the information and notes in our respective safety data sheets. The data contained herein are for informational purposes only and are believed to be accurate to the best of our knowledge. We assume no liability for the results. For optimum functionality of the adhesive system, please only use the cartridge and mixer systems tested and released by GLUETEC. The product is only suitable for professional and experienced users. It is the user's own responsibility to take precautions to protect property and people from the hazards that may be encountered in handling and using these products. Accordingly, GLUETEC specifically disclaims any warranty, expressed or implied, including any warranty or suitability commitments for a particular purpose. In particular, GLUETEC disclaims all liability for consequential or indirect damages of any kind.