

TECHNICAL DATA SHEET



AEROSOLS



Lubricate - Oil – Grease ADHESIVE GREASE SPRAY

WIKO HAFT-FETT-SPRAY is excellently suited for long-term lubrication of highly loaded bearings, spindles and guides due to an addition of corrosion and wear protecting additives and can be used for greasing and lubricating e.g. gears, gearboxes or wire ropes.

- high adhesion and thus good long-term effect Effective prevention of corrosion and wear
- Good high-pressure properties
- Temperature resistance: -30 °C to +200 °C

Application areas

- Grease lubrication of chains in the normal and high temperature range up to +200°C.
- Problem-free use for long-term lubrication
- Lubrication and corrosion protection for ropes, spindles, cylinders and other drive units, etc.

Sizes / article number

400 ml can AHFS.D400

Application

The surfaces to be coated must be free of dirt, rust, oils and greases. Use a suitable WIKO cleaner for this purpose (e.g. WIKO INDUSTRIESCHNELLREINIGER (Art. No. AISR.D400)). Shake can intensively before use (at least 2 minutes). Spray sufficiently from a distance of approx. 20 cm. Wait for penetration and spray again if necessary. Start up chains after sufficient flash-off time. After use, operate the can upside down until only propellant gas escapes.

Storage & Durability

The shelf life is, at the optimum storage temperature of +5 °C to +25 °C in the closed original container, a maximum of 12 months. A higher storage temperature leads to a significantly lower durability. The storage temperature must not fall below +5 °C.

Note:

Please note the information and notes in our respective safety data sheets. The data contained herein are for informational purposes only and are believed to be accurate to the best of our knowledge. We assume no liability for the results. For optimum functionality of the adhesive system, please only use the cartridge and mixer systems tested and released by GLUETEC. The product is only suitable for professional and experienced users. It is the user's own responsibility to take precautions to protect property and people from the hazards that may be encountered in handling and using these products. Accordingly, GLUETEC specifically disclaims any warranty, expressed or implied, including any warranty or suitability commitments for a particular purpose. In particular, GLUETEC disclaims all liability for consequential or indirect damages of any kind.